

Resources Secured by a JWT



To access the REST services listing swagger resource without having to enter the JWT beforehand, the `jwtSwaggerURI` property needs to be set with the aforementioned resource URI.

Example:

If the listing resource access URL is: <http://my.domain.com/<RootContext>/<CxfServlet>/swagger.json>, the URI to enter for the `jwtSwaggerURI` property is: `/<CxfServlet>/swagger.json` (for example: `/ws/swagger.json`)

If the listing resource access URL is: <http://my.domain.com/<RootContext>/<CxfServlet>/api-docs?url=/<RootContext>/<CxfServlet>/swagger.json>, the URI to enter for the `jwtSwaggerURI` property is: `/<CxfServlet>/api-docs/<CxfServlet>/swagger*` (for example: `/ws/api-docs/ws/swagger*`)

The swagger-ui `[api_key]` field may contain a JWT so that an `Authorization` header can be added to all the requests sent to the resource server.

Example:

Entering the following string into the swagger-ui field `[api_key]` (or `jwtKey [apiKey]`):

```
JWT eyJ0eXAiOiJKV1QiLCJhbGciOiJSUzI1NiJ9.eyJzdWUiOiJoYXkaXmIiLCJpc3MiOiJKV1RQcm92aWRicilsImhhdCI6MTQ2MzQwMzk2NCwiYXVkljoiaHR0cDovL2xvY2FsaG9zdDo4MDgwL2pheHJzliwianRpljoiaWRUb2t1b8xliwicm9sZXMiOiYWRtaW4iLCJ1c2VyaW4iOiJ1c2VyaW4iOj9X-G0np3zxeLt2BSfQxVSMxcCO4AUjSS21m72XD2fCMmQbJmnR86wT_IRIDkWXU0UowcDUOhEUYkmRhhMjN0vPsseWjgcXoj96vJ0X7cTxxpNSpjGmQteyz7lwL3iWkmUtNN-2OIHU4CSzUuj0JNnGfu3dMzC8vum_E81cT8IJDKxKyTV_NDrQQ2GKx8wGAPC9ZxAi_qBD3UHufv70vNEQUVka5azCMMnpAXIoBuZk0oeTPLITf4rYYCQ7WjsirzSylp8a47Xfgj_e6Qb-J01V9ohD5bgHvvB-fp63vT9dODPz_WKJO37_pdfvJALGlewzec0YU6iJUu5gQ
```

adds the following HTTP header to all requests sent to the resource server:

```
Authorization: JWT eyJ0eXAiOiJKV1QiLCJhbGciOiJSUzI1NiJ9.eyJzdWUiOiJoYXkaXmIiLCJpc3MiOiJKV1RQcm92aWRicilsImhhdCI6MTQ2MzQwMzk2NCwiYXVkljoiaHR0cDovL2xvY2FsaG9zdDo4MDgwL2pheHJzliwianRpljoiaWRUb2t1b8xliwicm9sZXMiOiYWRtaW4iLCJ1c2VyaW4iOiJ1c2VyaW4iOj9X-G0np3zxeLt2BSfQxVSMxcCO4AUjSS21m72XD2fCMmQbJmnR86wT_IRIDkWXU0UowcDUOhEUYkmRhhMjN0vPsseWjgcXoj96vJ0X7cTxxpNSpjGmQteyz7lwL3iWkmUtNN-2OIHU4CSzUuj0JNnGfu3dMzC8vum_E81cT8IJDKxKyTV_NDrQQ2GKx8wGAPC9ZxAi_qBD3UHufv70vNEQUVka5azCMMnpAXIoBuZk0oeTPLITf4rYYCQ7WjsirzSylp8a47Xfgj_e6Qb-J01V9ohD5bgHvvB-fp63vT9dODPz_WKJO37_pdfvJALGlewzec0YU6iJUu5gQ
```

NB: "JWT" is the default authentication scheme. If the `jwtAuthScheme` property of the `JwtTokenConfiguration` object requires another scheme, the string entered in the `[api_key]` field must be adjusted accordingly.

Click below for more information on the following topics:

- [Securing REST Web services](#)

[Top of page](#)